

UNAFLEX[®]

"Excellence In Manufacturing"

High Performance Marine Hose



Catalogue

MARINE WATER HOSE

Series 100

Premium Water Hose Hardwall

A premium water hose that is resistant to sea water, mild acids, toilet effluent, hot engine water, and external abrasion. Constructed with helical wire embedded between 2 plies of synthetic fabric for maximum flexibility.

SIZE 1/2" I.D. thru 1-3/8" I.D.

DESC. Black with green stripe.

PACKAGING 12-1/2ft. lengths. 50 ft. coils



Series 101

Premium Sanitation Hose

The premium sanitation hose designed for most critical toilet and holding tank connections with maximum resistance to toilet effluent and odor. Constructed with wire helix embedded between 2 plies synthetic fabric for maximum flexibility.

SIZE 3/4" I.D. thru 1-1/2" I.D.

DESC. Black with green stripe.

PACKAGING 12-1/2 ft. lengths. 50 ft. coils



Series 110

Premium Water Hose Softwall

A premium water hose that is resistant to sea water, mild acids, toilet effluent, hot engine water, and external abrasion. 2 ply construction where wire helix is not necessary for light bends.

SIZE 1/2" thru 1-3/8" I.D.

DESC. Black with green stripe.

PACKAGING 12-1/2ft. lengths. 50 ft. coils.



Series 120

Bilge Pump Hose

A corrugated polyethylene hose resistant to oily bilge and sea water. Designed for live well aerators, bilge discharge, sink, and shower drains. Durable, flexible, and abrasion resistant.

SIZE 5/8" I.D. thru 1-1/2" I.D.

DESC. Black or White

PACKAGING Bulk cartons, 50 ft. P/O cartons. Standard poly bags.



ELECTRICAL

Series 125

Electrical Conduit

A split wire conduit designed to provide chafing protection and quality appearance for multi-wire harness or cable routing. Also available in High Temperature Nylon.

SIZE 1/4" I.D. thru 2" I.D.

DESC. Black

PACKAGING Bulk cartons, 50 & 100 ft. P/O cartons



Series 127

Sternflex Hose

Sternflex hoses are primarily designed as a conduit hose for containing wires, control cables, and hoses between transom and outboard motor/sea drives when using a stern bracket. It can also be used for vanity sink and shower drains and is ideal for above water line scuppers.

SIZE 1-1/2" I.D. thru 2" I.D.

DESC. Gray, black & white

PACKAGING 50 ft. lengths.



Series 130/160

Standard / Extra Heavy Duty Water Hose

EPDM heater hose, 2 ply polyester reinforced for engine heater hose, heat exchanger, air conditioner circulation, and bilge. Also good for sink, icebox, shower, and live well drains. Meets or exceeds SAE.

20R3. Series 160 is an extra heavy duty hose with 4 ply construction for critical water application where high strength and durability are most important.

SIZE 1/2" I.D. thru 1-1/2" I.D.

DESC. Black with white letters

PACKAGING Bulk coils, 50 ft. P/O cartons, Standard poly bags.



Series 141

Lightweight Vinyl with Black Helix

A highly flexible FDA formulated clear PVC/ black helical-tubing for potable water fill, sink, bilge pump, shower, icebox, and live well drains (above the waterline).

SIZE 3/4" I.D. thru 1-1/2" I.D.

DESC. Clear with black helix.

PACKAGING 100ft. coils. 50 ft. P/O cartons.



Series 143

Sani-flex - H/D VAC

Heavy duty PVC hose with corrugated plastic helix that gives excellent flexibility and bend radius. Manufactured from FDA approved materials exhibiting low water absorption resulting in low odor permeation. Excellent for potable water, complete sanitation systems, and all systems. Use a Series 147 cuff.

SIZE 3/4" I.D. thru 1-1/2" I.D.

DESC. White / FDA Formulated.

PACKAGING 100 ft. coils. 50 ft. P/O cartons.



Series 147

Cuffs - H/D Sani - Flex

Right hand threaded soft PVC cuffs provide for added clamping protection when using Series 143 H.D. Corrugated Sani hose. For water tight seal apply with sealing compound.

SIZE 3/4" I.D. thru 1-1/2" I.D.

DESC. White

PACKAGING Each



Series 148

"Flex" Sanitation Hose Smooth H/D

A smooth wall extra heavy duty multi-purpose PVC hose especially formulated and compounded from FDA materials exhibiting low odor permeation. Excellent for all sanitation systems, below water drains, potable water, water intake systems, and aerators. Smooth cover permits clamping without cuffs. Recommended double clamps and sealing compounds for below waterline connections.

SIZE 5/8" I.D. thru 2" I.D.

DESC. FDA Formulated, White

PACKAGING 100 ft. coils. 50 ft. P/O cartons. Standard poly bags



Series 149

Live Well Hose

An extra heavy duty walled all vinyl hose with hard PVC helix, smooth inside and outside, that gives good flexibility and bend radius.

For live well intake and drain also excellent for bilge pump discharge and drain lines. Smooth wall permits easy clamping. Formulated with FDA type materials.

SIZE 5/8" I.D. thru 1-1/2" I.D.

DESC. Clear with black helix. Also solid black

PACKAGING 100 ft. coils. 50 ft. P/O cartons



WATER HOSE

Series 150



Clear PVC Tubing

A clear FDA formulated PVC tubing for low pressure cold water applications in sink, shower, refrigerator, and live well drain lines.

SIZE 1/4" I.D. thru 1-1/2" I.D.

DESC. Clear

PACKAGING 200 ft. coils. 25 & 50 ft. PVO cartons. Standard poly bags.

Series 162, 163, 164



Red - Clear - Blue - PVC Reinforcement Tubing

A heavy walled, nylon reinforced PVC tubing compounded with FDA formulated materials for applications requiring non-toxic, tasteless, odorless tubing. Hot or cold pressurized systems. Vent and drain lines, bilge pump discharge. 162 Red tracer for hot and cold tap water. 163 Extra heavy wall. 164 Blue tracer for cold tap water.

SIZE 3/8" I.D. thru 2" I.D.

DESC. Red Tr - 162. Clear - 163. Blue Tr - 164

PACKAGING 250 ft. coils. 50 ft. PVO cartons. Standard poly bags

Series 166



Boat & Camper Hose

FDA formulated premium drinking water and superior dock side wash down hose. Braided reinforcement and coupled with brass full flow couplings.

SIZE 5/8" I.D.

DESC. White

PACKAGING Lengths of 25, 50, 75 & 100 ft

EXHAUST HOSE

Series 200



Certified Wet Exhaust Softwall SAE J2006 R1

Certified wet exhaust, heavy wall reinforcement with 2, 4, or 6 plies of synthetic cord. Designed for engine water circulation, heat, heat exchanger, heavy duty discharge lines and straight marine wet exhaust connections. Meets or exceeds USCG, ABYC, and SAE J2006 R1 standards for wet exhaust service. Recommended for short straight connections.

SIZE 1-1/2" I.D. thru 16" I.D.

DESC. Black with blue stripe.

PACKAGING 50 ft. coils thru 3". 12-1/2 ft. lengths.

Series 250



Certified Wet Exhaust Hardwall SAE J2006 R2

Certified wet exhaust, heavy wall with helical wire reinforcement between (4) plies of rayon fabric. Compounded to resist engine heat, exhaust fumes, ozone, mild acids, toilet effluent, salt water, and abrasion. Meets or exceeds USCG, ABYC, and SAE J2006 R2 standards for wet exhaust service.

SIZE 1/2" I.D. thru 8" I.D.

DESC. Black with blue stripe.

PACKAGING 50 ft. coil thru 8" I.D. 12-1/2 ft. lengths.

Series 252



Corrugated Wet Exhaust SAE J2006 R2

Corrugated wet exhaust, heavy wall with helical wire reinforcement between (4) plies of rayon fabric. Compounded to resist engine heat, exhaust fumes, ozone, mild acids, toilet effluent, salt water, and abrasion. Meets or exceeds USCG, ABYC, and SAE J2006 R2 standards for wet exhaust service. Available for Severe-Bend Applications.

SIZE 1-1/2" I.D. thru 8" I.D.

DESC. Black with Blue stripe.

PACKAGING 50 ft. coil thru 4" I.D. 12-1/2 ft. lengths.

FUEL HOSE

Series 315



"Flex-Acol" Alcohol Resistant Type B fuel

Excellent resistance to heat, ozone, and permeation by alcohol blended gasoline and diesel fuels. Compounded to meet or exceed SAE J1527 Type B, USCG - Type B, USCG and NMMA standards for fuel feed and vent hoses. Multiple plies of reinforcement provide superior flexibility and good bend radius.

SIZE 1/4" I.D. thru 5/8" I.D.

DESC. Black with red lettering.

PACKAGING 250 ft. coils. Standard PVO cartons. Standard poly bags.

Series 350 - 360



"Flex-Acol" Alcohol Resistant Type A Fuel

Excellent resistance to fire, heat, ozone, and permeation by alcohol blended gasoline and diesel fuels. Compounded to meet or exceed SAE-J1527 Type A, ISO/DIS 7840, USCG and NMMA standards for fuel feed, fill and vent hoses. 1-1/2" I.D. thru 2-3/8" I.D. has wire helix for excellent flexibility.

SIZE 1/4" I.D. thru 2-3/8" I.D.

DESC. Black with red lettering or stripe.

PACKAGING 250 ft. coils 1/4" thru 1/2". 150 ft. coils thru 5/8". 100 ft. coils thru 3/4". Standard PVO cartons. Standard poly bags.

VENT & DUCTING

Series 400



Blower Vent

PVC blower vent hose supported by copper plated wire helix and resistant to ozone, sunlight and weathering. Does not support combustion.

SIZE 3" I.D. thru 4" I.D.

DESC. Black or white

PACKAGING 50 ft. cartons. Standard poly bags.

Series 420



Blower Vent - Heavy Duty

Heavy duty PVC blower vent hose with vinyl coated wire helix per UL specifications. Resistant to ozone sunlight and weathering. Will not support combustion.

SIZE 3" I.D. thru 4" I.D.

DESC. Black

PACKAGING Bulk Cartons.

Series 460



Non - Insulated A/C Ducting

Heavy duty PVC fabric reinforced A/C ducting with nylon and a metallic helix to insure maximum air flow and minimum condensation. Resistant to ozone sunlight. Manufactured to meet or exceed UL Class 1 standards of flame resistance.

SIZE 3" I.D. thru 7" I.D.

DESC. Gray

PACKAGING 25 ft. lengths. Bulk packaging.

Series 480



Insulated A/C Ducting

Insulated A/C ducting manufactured to meet or exceed UL Class 1 standards of flame resistance.

SIZE 3" I.D. thru 7"

DESC. Aluminized exterior with heavy fiberglass insulation.

PACKAGING 25 ft. lengths. Bulk packaging.

UNAFLEX MARINE PRODUCTS DIVISION

ACCESSORIES

DESCRIPTION OF UNAFLEX PART NUMBERS

Series 720



"T-Bolt" Exhaust Hose Clamps

A marine grade all 316 stainless steel hose clamp designed to assure proper clamping of large diameter marine exhaust hose. All clamps are equipped with a nylon insert lock nut.


SIZE 1" thru 16" standard hose I.D.

DESC. Stainless steel

PACKAGING 10 each package

UNAFLEX utilizes a seven digit part number system that designates the hose series, the hose I.D. and the length of the hose.

The first three digits indicate application. The three digits after application indicate size. The last digit shows length of hose package.



LAST DIGIT:

0 = bulk	1 = 6 ft.	2 = 9 ft.	3 = 10 ft.
4 = 12-1/2 ft.	5 = 25 ft.	6 = 50 ft.	7 = 100 ft.

FOR INFORMATION, TECHNICAL HELP OR,
TO PLACE AN ORDER
CALL OUR TOLL FREE NUMBER
1-800-624-9242
OR
FAX- 954-781-5985
E MAIL- sales@unaflex.com

Series NF



Nylon Hose Nipples

Nylon hose nipples designed to accommodate all rubber and plastic hoses in the marine industry. Fittings are sized at the hosebarbs to fit PVC hoses.

SIZE 1/2" thru 2" I.D. Hose sizes

DESC. White Nylon

PACKAGING Each

Brass Hose Fittings, Ferrules and Adapters



Brass hose fittings and brass ferrules designed to accommodate all sizes of fuel feed and vent hoses in the marine industry.

SIZE 1/4" I.D. thru 3/4" I.D. hose sizes

DESC. Solid Brass

PACKAGING Each

"UNAFLEX" A COMPANY COMMITTED TO MANUFACTURING EXCELLENCE



PERFORMANCE TESTED

*THE UNAFLEX SPONSORED FOUNTAIN FLYER
HEADED FOR VICTORY*

Distribution Centers in Houston, Tx & Pompano Beach Fl

Sales & Corporate Headquarters:

Unaflex Marine Division
3901 NE 12th AVE
Pompano Bch, Fl 33064

Call Toll Free 1-800-624-9242

Fax 954-781-5985

Local 954-783-3373

E-mail sales@unaflex.com

visit our website at www.unaflex.com